



www.secap.com

Secap® Color Digital Printer

SAY IT WITH COLOR!



Model SL 600

Setting New Standards in Mailstream Productivity

The Secap® Color Digital Printer is the new cost effective solution for printing on-demand, full color envelopes, cards, and sheets.

- Speeds up to 3,300 full color #10 envelopes per hour, 500,000+ per month
- Print envelopes to 13" x 17" and sheet up to 13" x 22"
- Average consumable cost per full color #10 envelope is only 2¢
- Prints variable data at full speed for optimum productivity
- High capacity sheet feeder holds up to 600 envelopes or 4,000 sheets of 20lb. bond

Secap® Color Digital Printer

TECHNICAL SPECIFICATIONS

Print Method: Electrophotographic, single pass, digital printer

Print Speed*: From the paper cassette; Color: up to 36 ppm; Monochrome: up to 40 ppm; Envelope Feeder, 60 envelopes

Warm-up Time: Up to 85 seconds

First Page Output Time: Color: 10.5 seconds from an idle, ready state on plain paper; Monochrome: 9 seconds from an idle, ready state on plain paper

Resolution: 600 x 1200 dpi

Recommended Duty Cycle: 150,000 prints per month maximum (industry standard letter/A4 at 5%)

HARDWARE AND SOFTWARE CAPABILITIES

Processor Type: PowerPC 750FX, 800 MHz

Memory: 1 GB standard

Operating System Compatibility: Windows: Windows® XP Professional, XP Home, 2003 Server; Windows 98, 98 SE, ME, NT® 4.0 Workstation, NT 4.0 Server (SP6 or later), 2000 Workstation (SP3 or later), 2000 Professional (SP3 or later), 2000 Server (SP3 or later), 2000 Advanced Server (SP3 or later); Citrix® MetaFrame® – Windows 2000 Server (ServicePack4) with Citrix MetaFrame XP® Presentation Server Feature Release 3, Windows Server 2003 Standard Edition with Citrix MetaFrame XP Presentation Server Feature Release 3; Macintosh: Mac® OS 9.x, Mac OS 10.2.4 – 10.4.2; Unix/Linux

Printer Languages: Adobe PostScript 3, PDF v.1.4 Emulations: PCL®5c, PCL 6, IBM PPR, EPSON FXDirect PDF Printing (Windows only) Printer Management: Printer Drivers, Color Correct Utility, Color Swatch Utility, PDF Direct Print, Profile Assistant, PS Gamma Adjuster, Storage Device Manager, Admin Manager/Quick Setup, LPR Utility, Network Printer Status

INTERFACE SUPPORT

Standard: 10/100-TX Ethernet, High-speed USB v2.0, Parallel

Ethernet Protocols: TCP/IP, Netware and Ethertalk. TCP/IP includes ARP, IP, ICMP, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMP, DNS, SSL/ TLS, JetDirect protocols; Netware includes 3.x, 4.x, 5.x, and 6.x with full NDS and NDPS support – PServer, RPrinter, NDPS supported via dedicated NDPS Gateway. EtherTalk: ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP.

*Print Speed varies depending on system configuration, software application, driver, thickness of stock and document complexity. Specifications subject to change without notice.

PAPER HANDLING

Standard Paper Input: 530 sheets + universal tray

Envelope Input Feeder: 600 Com #10 envelopes; 4,000 sheets (20lb bond)

Delivery Stacker: Variable speed conveyer belt

Paper Size Supported: Universal Tray: Tabloid extra (12" x 18"), tabloid, legal, letter, executive, index cards, A3, A3 wide (12.6" x 17.7"), A3 outsize (12.9" x 17.8"), A4, A5, A6, B4, B5, C5, DL; Feeder: Sheets and Envelopes (min: 5.125" x 4.125" or 130.2mm, max: 13" x 22" or 330.2mm x 558.8mm) Paper Weights: Universal Tray supports 75-216 gsm, up to 50 lb. text and 80 lb. cover; Feeder supports 75-308 gsm, up to 14 point cover

Print Media: Plain paper, letterhead, coated, uncoated, linen, specialty stocks

Window Envelopes: Glassine, Earth First PLA, Digi-Clear™, open window (Poly Window Envelopes are NOT supported)

PHYSICAL

Type: Digital envelope press with internal Adobe PostScript controller

Dimensions (WxDxH): including delivery conveyer; 92" x 24.4" x 18.2" (233 cm x 62.0 cm x 46.2 cm)

Weight: 152 lb. (69.0 kg) without options

ELECTRICAL

Power Requirements: 120 (110 – 127) VAC; 60 Hz ± 2 Hz; 230 (220 – 240) VAC; 50 Hz, ±2 Hz

Power Consumption: Operating: 750W; Standby: 200W; Power Save Mode: 55W

ENVIRONMENTAL

Temperature Requirements: Operating: 50-90° F (10-32° C); Non-operating: 32-110° F (0-43° C); Best Print Quality: 63-80° F (17-26° C)

Humidity: Operating: 20-80% RH; Non-operating: 10-90% RH; Best Print Quality: 50-70% RH

Noise Levels: Operating: 53 dB; Standby: 40 dB; Power Save Mode: 40 dB

CONSUMABLES

In-Box Cartridges: Printer ships with one each cyan, magenta, yellow and black toner cartridge; cyan, magenta, yellow and black image drum; waste toner box, fuser unit, and transfer belt

TYPEFACES

136 Adobe PostScript Type 1 typefaces, 86 scalable PCL fonts, 1 bitmap font, 10 TrueType® fonts, OCR A/B, USPS Barcode



Available from your authorized and certified Secap dealer.

MILLENNIUM MAILING EQUIPMENT
84 HARRIS ST
PAWTUCKET, RI 02861-1719
Tel. 401-729-1131
Fax 401-729-1133
email: info@millennium-mailing.com
www.millennium-mailing.com

Contact the dealer above

© Xante, Symphony Workow, SpeedSetter, KoolKolor, KoolToning, StripRITE, PerfectBLEND, AdvancedScan, RasterView, TrapZone, ImagerQ Concerto, VM, Harmony Violet Metal Plates, Harmony Violet CTP Developer, Harmony Violet CTP Replenisher, Harmony Litho Processor Cleaner, and Harmony Litho CTP Gum are trademarks or registered trademarks of Xanté Corporation. Adobe, PostScript 3, APPE and Accurate Screens are registered trademarks of Adobe Systems, Incorporated, which may be registered in certain jurisdictions. Fiery is a registered trademark of EFI. All other trademarks or registered trademarks are the property of their respective owners. Prices and equipment specifications subject to change without notice